

SONIC® 4-STROKE SL

SYNTHETIC POWER SPORT ENGINE OIL

PRODUCT DESCRIPTION

SONIC® 4-STROKE SL is a premium, full-synthetic 4-stroke motor oil. It is designed specifically for non-automotive, high-output/high RPM power-sport motors. SONIC® 4-STROKE SL combines a unique blend of fully synthetic polyalphaolefin (PAO) base oils and industry-leading additives. This combination ensures a superior level of protection in applications that can produce RPM levels near double that of their automotive counterparts.

PERFORMANCE FEATURES

- 100% synthetic formulation
- Wet clutch compatible
- Superior operating range -35°C to 35°C
- Hyper ZDDP technology provides wear protection and catalyst life
- Improved engine cleanliness
- Exceptional corrosion protection

APPLICATIONS

SONIC® 4-STROKE SL is engineered to withstand the punishment endured by high performance engines in the following: snowmobiles, ATVs, motorcycles and outboard motors. This product is also suitable for use in 4-stroke snow throwers, generators, lawn mowers and garden tractors.

TECHNICAL PROPERTIES

The values listed below are typical of current production. As variations may occur, these numbers do not constitute a specification.

PROPERTIES	TEST METHODS	SAE 5W-50
Kinematic Viscosity cSt @ 40°C	ASTM D445	99.8
Kinematic Viscosity cSt @ 100°C	ASTM D445	16.5
Viscosity Index	ASTM D2270	175
Pour Point, °C	ASTM D97	-60°

Technical Data Sheet: SONIC® 4-STROKE SL Rev date: September 2018

^{*} This product does not contain friction modifiers. Most non-automotive/power sport applications require lubricants manufactured in this manner.

PERFORMANCE SPECIFICATIONS

SONIC® 4-STROKE SL meets or exceeds OEM engine oil warranty requirements in applications calling for the following:

INDUSTRY/OEM	SPECIFICATIONS
API	SM
JASO	MA
NMMA	FC-W
	FC-W Catalyst Compatible

MATERIAL SAFETY DATA SHEETS

Product-specific material safety data sheets (MSDS) can be obtained by contacting your local retail co-op or Federated Co-operatives Limited (see contact information below) or by going online at coopconnection.ca

PRODUCT SELECTION

Product availability can vary by location. Please contact your local retail co-op for further details.

PRODUCT SIZES	5W-50
1 L Bottle	✓
5 L Bottle	
10 L Bottle	
20 L Pail	
110 L Drum	
205 L Drum	
1000 L Tote	

RECYCLING OF USED LUBRICANTS AND CONTAINERS

Please protect the environment when disposing of petroleum products. All products should be taken to an authorized collection facility or picked up by a qualified organization. This ensures the products will be disposed of in an environmentally sensitive manner. For additional information on used-oil recycling programs, please see the following:

- Saskatchewan www.usedoilrecyclingsk.com
- Alberta www.usedoilrecyclingab.com
- British Columbia www.bcusedoil.com
- Manitoba www.usedoilrecycling.com/en/mb

CONTACT INFO

For more information on this or any other CO-OP" lubricant product, please contact your local retail co-operative or Federated Co-operatives Limited.





